2

CLAIM AMENDMENTS

IN THE CLAIMS

This listing of the claims will replace all prior versions, and listing, of claims in the application or previous response to office action:

- 1. (Original) A direct-to-digital holography system, comprising: an illumination lens operable to focus a reference beam:
- a beam splitter optically coupled to the illumination lens by the reference beam; and

a reference mirror located at a waist of the reference beam, the reference beam mirror operable to eliminate a reference objective.

- (Original) The system of Claim 1, wherein the beam splitter comprises a cube beam splitter operable to eliminate first order reflections.
- (Original) The system of Claim 1, further comprising a quarter-wave plate optically coupled between the beam splitter and the reference mirror.
- (Original) The system of Claim 1, wherein the reference beam comprises a Gaussian beam.
- (Original) The system of Claim 1, wherein the reference mirror comprises a flat mirror.
- (Original) The system of Claim 1, further comprising the reference mirror operable to maintain optical symmetry of a reference arm and a target arm.
- (Original) The system of Claim 1, further comprising the reference mirror operable to form a first wavefront substantially similar to a second wavefront formed by the reference objective.

3

 (Original) A method for acquiring a complex image in a direct-todigital holography system, comprising:

focusing a reference beam with an illumination lens, the reference beam including a waist;

transmitting at least a portion of the reference beam through a beam splitter;

reflecting the portion of the reference beam from a reference mirror located at the waist of the reference beam.

- (Original) The method of Claim 8, further comprising the reference mirror operable to replace a reference objective.
- 10. (Original) The method of Claim 9, further comprising forming a combined wavefront at a digital recorder, the wavefront substantially similar to a wavefront produced by the reference objective.
- 11. (Original) The method of Claim 8, further comprising the reference mirror operable to maintain optical symmetry of a reference arm and a target arm.
- (Original) The method of Claim 8, wherein the reference beam comprises a Gaussian beam.

13-32. (Canceled)